



SOLVENT FREE ADHESIVE DOUBLE SIDE TAPE

Product no.	Thickness	Carrier, Color	Liner	Peel Adhesion (gf/25mm)	Shear adhesion (kgf/cm ²)	Temperature resistance
3505	50 μm	PET/Transparent	PET	1600	4.5 kgf/cm ²	120°C
3508	80 μm	PET/Transparent	PET	1800	5.0 kgf/cm ²	150°C
3510	100 μm	PET/Transparent	PET	1900	5.5 kgf/cm ²	150°C
3515	150 μm	PET/Transparent	PET	2000	6.0kgf/cm ²	150°C
3520	200 μm	PET/Transparent	PET	2100	5.5 kgf/cm ²	150°C
3540	400 μm	PET/Transparent	PET	2200	5.0 kgf/cm ²	150°C
3505B	50 μm	PET/Black	PET	1600	4.5 kgf/cm ²	120°C
3508B	80 μm	PET/Black	PET	1800	5.0 kgf/cm ²	120°C
3510B	100 μm	PET/Black	PET	1900	5.5 kgf/cm ²	120°C
3515B	150 μm	PET/Black	PET	2000	6.0kgf/cm ²	120°C
3508BD	80 μm	PET/Black	PET	1800/1000	6.0 kgf/cm ²	120°C
3510BD	100 μm	PET/Black	PET	1900/1000	5.5 kgf/cm ²	120°C
3505BW	50 μm	PET/Black & White	PET	1600	4.5 kgf/cm ²	120°C
3508BW	80 μm	PET/Black & White	PET	1800	5.0 kgf/cm ²	120°C
3510BW	100 μm	PET/Black & White	PET	1900	5.5 kgf/cm ²	120°C